

Release Notes GC-PowerStation v6.4

Table of Contents

- NEW FEATURES..... 2**
 - MICRONS ADDED AS A STANDARD UNIT 2
 - INCREASED THE MAXIMUM NUMBER OF ALLOWED LAYERS 2
- ENHANCED FEATURES..... 2**
 - FILTER SELECTION 2
 - GC-BASIC FUNCTIONALITY 2
 - ON LINE HELP 2
- ITEMS FIXED SINCE V6.3.2 3**

New Features

Microns added as a standard unit

Microns have been added to all products as a standard unit throughout the job. The addition allows for the importing of certain DXF and DWG files that were designed in microns as well as providing direct measurements in microns throughout the application.

Increased the maximum number of allowed layers

The maximum number of allowable data layers has been increased to 1024 from 256. While most users come nowhere near this upper limit, occasionally certain imported files are written in such a way that they previously overflowed the upper bounds of the software layer count.

Enhanced Features

Filter Selection

The Shape field in the Filter selection dialog now allows the selection of Chamfered Rectangles, Diamonds and other formula custom apertures.

GC-Basic functionality

Improvements to the Copperless Drill function have been added.

Added new global GCB function

GetRunningScriptName() to determine the name and path of a script.

On Line Help

As always the On Line Help has been updated to include these new and enhanced functions.

Items Fixed since v6.3.2

This list is customer reported issues fixed for this release.

#3734 Enhancement to contour engine algorithm fixes a Netlist Extract crash.

#3732 Enhancement to contour engine algorithm fixes a Netlist Extract crash. Problem was caused by offsetting holes in isolated oblong pads.

#3726 Corrected an issue regarding the mitering of traces in an AutCAD DXF output. Previously, certain traces were incorrectly mitered and caused an incorrect image.

#3725 Isolation failure due to incorrectly calculated contour has been corrected.

#3724 Added a new build configuration in order to allow the release of all GraphiCode products using Simplified Chinese characters.

#3721 The ability to check Routed or Drilled slots has been added to the Copperless Drill function. The ability to access this function through GC-Basic has been added.

#3718 As a side effect of contour algorithm work The application no longer crashes during the Solder Bridging check on this dataset.

#3716 Updated the GC-Basic syntax for assigning inner layer DFM values through the scripting interface.

#3715 Netlist Extraction no longer crashes the application on this dataset. The fix is due to enhancements to the contour calculation.

#3714 Enhanced the PTH To Copper check to allow error finding on arcs as well as vectors for this dataset.

#3713 The informational message that informed the user that a different font was being used for DXF or DWG text (when the specified font was not available) now only appears once. Previously it was appearing for every text string specified.

#3709 Netlist Extraction no longer fails to connect the selected pad and trace in the dataset. The fix is due to enhancements to the contour calculation.

#3708 A small utility program has been created and added to the website for verifying that a dongle is still correctly stamped with a key number. This utility can be used to verify if a Superpro dongle has failed in the field. Customers with a current Annual Support Plan will of course have faulty dongles swapped at no charge.

#3701 Fixed a bug that caused an incongruity between job units and DFM Setup units that manifested itself in the Minimum Feature DFM check.

#3700 The Maximum Via Diameter is now correctly saved in the DFM settings. The problem was caused by the introduction of the HFlexGrid.

#3699 Added a field to allow for a user-definable path for the output of Image files from the Export menu. The field is contained in the Tools>Customize>File Locations dialog.

#3698 The setting for retaining File Extension name when importing layers is now stored in the registry rather than in the GWK.

#3695 Updated the teardropping algorithm to correctly create fillet teardrops on rectangular pads. Previously the fillet width was a factor of two too small.

#3694 Added new global GCB function GetRunningScriptName() to retrieve the currently running script.

#3693 Removed rogue Registry key and value name from the string table. This had been causing weird behavior in the Japanese version.

#3689 Fixed a data specific application crash that occurred when the Unterminated Trace DFM check was run.

#3687 ODB++ file now correctly loads rounded rectangles that are at non-orthogonal angles.

#3686 When Remove Inner Unused Pads is run on more than 6 inner layers, a range error occurred that has been fixed for this release.

#3679 Updated the contour engine to handle the isolation of a custom aperture constructed with a slit.

#3676 Allow filter selection to select more shapes (see Enhanced Features section).

#3667 Non ASCII characters are now handled in the Export dialog. Previously when outputting RS-274X files that contained an Umlaut in their filename were not output.

#3660 An option has been added to the Tools > Customize > Settings dialog to display the full filename and path in the application window.

#3658 Added a warning during Import RS-274X to flag the presence of zero dimension apertures.

#3657 Isolation failure due to incorrectly calculated contour has been corrected.

#3656 Internal Error message no longer occurs after closing a minimized application.

#3653 Modified Allegro drill header recognition code to recognize the slight change in format for the newer version (old version still recognized as well).

#3652 Added the option to Select All errors during the DFM Review operation.

#3651 We now order DFM errors from smallest to largest by default in the DFM Review dialog.

#3640 Fixed a minor issue where focus was not being updated correctly when Enter was used within the New Aperture size dialog.

#3639 Removed the redundant 'Smart R90' entry in the Rotate dialog.

#3633 Modified code designed to ignore whitespace characters within aperture macros; code was overstepping its bounds in ignoring these characters within the name field.

#3626 Updated the Reorder Polygon function to ignore polygon constructions with the Void Fill attribute assigned.

#3625 Added a field to define the location to save CAP files created when using the Advanced Scan and Replace function.

#3619 Correctly recognize Sieb and Meyer rout file by ignoring characters that were previously being considered.

#3618 Save Setup Tab Settings in RS274X Output Dialog

#3614 Fixed a nasty release only bug concerning the fill function applied with outline replacement and Edge Adjust.

#3611 The following updates have been made to the IPC-D-356 output

- skip iterating pads from composite layers
- skip iterating pads from inner layers
- remove buried drilled pads from output
- remove the pad from buried end of blind drills from output

#3609 Updated the Arc to Vector algorithm to retain polygon ordering following completion.

#3604 Disabled panelization checking code in RS274x and MDA Fire outputs. We now no longer produce a message questioning the step and repeats of the data layers compared to the drill layer.

#3601 The Fix Voids function has been moved from the DFM category checklist in the DFM Setup dialog and can now be found on the Right button mouse menu within the DFM Results. When a void is fixed, the

polygon that creates the fill is tagged with the Void Fill attributes.

#3600 Updated the Fix Voids function to deal with a void created by a composite layer by creating the fill on a new positive data layer automatically created above the offending composite layer.

#3575 Increased the maximum number of data layers allowed in the application (see above)

#3517 Import of this particular DWG file no longer hangs the application.

#2492 Netlist Extraction no longer crashes the application on this dataset. The fix is due to enhancements to the contour calculation.

#634 Add Microns as an option for units (see above)